

RFA30NFFdB



INPUT POWER: 30 Watts

PERFORMANCE SPECIFICATIONS:

Frequency Range: DC to 2.4 GHz
VSWR: 1.15:1 - DC to 1.0 GHz
1.35:1 - 1.0 to 2.4 GHz
Attenuation Value: 3 to 30 dB
Attenuation Accuracy: ± 0.30 dB or 3%
Peak Power: 2 kW max.
Nominal Size: (L,W,H) 3" x 2 1/2" x 2 1/4" max.
Weight: 3/4 lbs. (.35 kg) max.

RFA60NFFdB




INPUT POWER: 60 Watts

PERFORMANCE SPECIFICATIONS:

Frequency Range: DC to 2.4 GHz
VSWR: 1.15:1 - DC to 1.0 GHz
1.35:1 - 1.0 to 2.4 GHz
Attenuation Value: 3 to 30 dB
Attenuation Accuracy: ± 0.30 dB or 3%
Peak Power: 2 kW max.
Nominal Size: (L,W,H) 3" x 2 1/2" x 2 1/4" max.
Weight: 3/4 lbs. (.35 kg) max.

RFA100NFFdB




INPUT POWER: 100 Watts

PERFORMANCE SPECIFICATIONS:

Frequency Range: DC to 2.4 GHz
VSWR: 1.15:1 - DC to 1.0 GHz
1.35:1 - 1.0 to 2.4 GHz
Attenuation Value: 3 to 30 dB
Attenuation Accuracy: ± 0.30 dB or 3%
Peak Power: 2 kW max.
Nominal Size: (L,W,H) 7 1/2" x 4 1/4" x 4 1/4" max.
Weight: 4 lbs. (1.81 kg) max.

RFA150NFFdB



INPUT POWER: 150 Watts

PERFORMANCE SPECIFICATIONS:

Frequency Range: DC to 2.4 GHz
VSWR: 1.15:1 - DC to 1.0 GHz
1.35:1 - 1.0 to 2.4 GHz
Attenuation Value: 3 to 30 dB
Attenuation Accuracy: ± 0.30 dB or 3%
Peak Power: 2 kW max.
Nominal Size: (L,W,H) 7 1/2" x 4 1/4" x 4 1/4" max.
Weight: 5 lbs. (2.27 kg) max.